



Provided by Xpert Survey Equipment  
[Click Trimble Geo Explorer for Product Info and Updated Pricing](#)

### Key Features

#### 220 channel GNSS receiver

Submeter real-time and 50 cm postprocessed accuracy

#### Floodlight satellite shadow reduction technology option

More positions and increased accuracy in tough environments

#### Sunlight readable display

4.2" polarized screen for unmatched clarity in bright sunlight

#### 3.5G modem option

Integrated cellular for Internet connectivity in the field

#### 5 megapixel autofocus camera

Capture high quality photographs and link directly to features

#### Field swappable battery

More than 8 hours operation on a single charge and swap-and-go battery replacement in the field

### A New Standard For Productive GNSs Data Collection

The Trimble® GeoExplorer® 6000 series takes GNSS productivity to a whole new level. Combining submeter accuracy GNSS, high quality photo capture, wireless Internet, and connectivity options in a single product, the GeoXT™ handheld is the ideal field device for organizations mapping critical assets and infrastructure, or for anyone needing dependable submeter accuracy GNSS data, simple operation, and repeatable results.

Together with the latest field software enhancements and GNSS innovations—including Trimble Floodlight™ satellite shadow reduction technology—the GeoXT handheld is the ideal submeter field solution for any industry, including utility companies, local government organizations, and federal agencies.

#### Reliable submeter performance

Integrating the latest in Trimble GNSS receiver technology, with the optional ability to track both GPS and GLONASS satellites, the GeoXT handheld delivers consistent submeter accuracy in real time and 50 cm accuracy after postprocessing.

For submeter accuracy, the GeoXT handheld's integrated SBAS receiver can be used to obtain real time corrections such as WAAS, EGNOS, or MSAS, or the GeoXT handheld's built-in Bluetooth® wireless technology can be used to seamlessly connect to a Trimble GeoBeacon™ receiver.

For 50 cm accuracy, data collected with Trimble field software can be postprocessed using the Trimble GPS Pathfinder® Office software or GPS Analyst™ extension for Esri ArcGIS Desktop software. These office processing suites use Trimble DeltaPhase® technology to achieve 50 cm accuracy for GNSS code measurements after postprocessing, and even higher levels of postprocessed accuracy are possible if GNSS carrier data is logged for extended periods.

#### Floodlight satellite shadow reduction

Trees and buildings create shadows, limiting the environments where reliable high-accuracy GNSS data collection can be performed. Using the innovative Trimble Floodlight satellite shadow reduction technology, the GeoXT handheld continues to deliver productive, usable positioning data in areas where legacy GNSS receiver systems cannot.

With the optional Floodlight technology option installed, the GeoXT receiver can compute positions even with very weak satellite signals. Floodlight technology increases the number of positions that are gathered in difficult locations, and boosts accuracy in those places where normally only low accuracy data is available. With the GeoXT handheld, field crew can now work with fewer disruptions, meaning better data, faster, at less cost.

#### Never-seen-before display performance

The GeoXT handheld includes a sunlight-optimized, display designed specifically for outdoor operation. It maintains exceptional clarity in all outdoor conditions, including direct sunlight. Text is crisp and easy to read. Background maps and photos are rich and vibrant. At 4.2" (10.7 cm), the display is also big, so the touch panel is spacious and easy to control.

#### Work online, anywhere

Internet access in the field gives workers live access to the information they need to make better decisions, faster. Once connected, field workers can collaborate with their office and with each other, even from remote locations.

The GeoXT handheld offers a choice of wireless technology to enable Internet connections directly on the device—including an optional 3.5G cellular modem built into the handheld itself, integrated Wi-Fi, or Bluetooth wireless technology.

Whether connecting to corporate networks, or accessing web-based services such as real-time map data or VRS™ corrections, accessing and updating live information in the field is simple and fast.

Bluetooth technology also enables wireless connection to other external devices such as Bluetooth-enabled laser range finders, barcode scanners or RFID readers.

#### High quality photo capture

A photograph is often the best way to capture information about an asset, event, or site. The GeoXT handheld includes a 5 megapixel autofocus camera with geo-tagging capability. The camera can be controlled by the TerraSync™ software and other third party applications, so photo capture and linking of images to GIS features is seamless and simple to integrate with existing data capture workflows.

#### Designed for work

The GeoExplorer 6000 series was designed with a single goal in mind—delivering a high-accuracy handheld GNSS system that works faster, longer, and in more places than any other.

The Lithium-Ion battery provides up to 8 hours of GNSS operation on a single charge, and can be swapped on-the-go without shutting down the device—enabling near-continuous operation and minimizing field worker downtime.

The GeoXT handheld is powered by a super-fast OMAP 3503 series processor and 256 MB RAM. With 2 GB of internal storage and the capacity to add an additional 32 GB via SDHC card, the GeoXT handheld has the capacity and power you need to work with high resolution maps and complex datasets.

The fully ruggedized IP65 construction is designed to withstand the harshest environments. Wherever field workers go, they can take the GeoXT handheld with the confidence that the equipment can handle the toughest conditions.

These smart design features combine with unprecedented accuracy and productivity to deliver the ultimate high performance handheld field solution.

The GeoXT handheld. Designed for work.



# geoexplorer 6000 series geoxT handheld

## system summary

- Single-frequency GNSS receiver with Everest™ multipath rejection technology and optional Trimble Floodlight satellite shadow reduction technology
- Sunlight readable 4.2" polarized screen
- Optional integrated 3.5G cellular and Bluetooth wireless technology
- 5 megapixel autofocus camera
- Windows 6.0 Professional edition
- Rugged and water-resistant design

## size and weight

Height . . . . . 234 mm (9.2 in)  
 Width . . . . . 99 mm (3.9 in)  
 Depth . . . . . 56 mm (2.2 in)  
 Weight (inc. battery) . . . . . 925 g (2.0 lb)

## GNSS

Receiver . . . . . Trimble Maxwell™ 6 GNSS chipset  
 Channels . . . . . 220 channels  
 Systems . . . . . GPS, GLONASS, SBAS  
 GPS . . . . . L1C/A  
 GLONASS . . . . . L1C/A, L1P  
 SBAS . . . . . WAAS/EGNOS/MSAS  
 Update rate . . . . . 1 Hz  
 Time to first fix . . . . . 45 s (typical)  
 NMEA-0183 support . . . . . Optional  
 RTCM support . . . . . RTCM2.x/RTCM3.x  
 CMR support . . . . . CMR/CMR+/CMRx

## GNSS accuracy (HRMS) after correction

Real-time code corrected  
 VRS or local base . . . . . 75 cm + 1 ppm  
 SBAS (WAAS/MSAS/EGNOS) . . . . . < 1 m  
 Code postprocessed . . . . . 50 cm + 1 ppm  
 Carrier postprocessed<sup>3</sup>  
 After 10 minutes . . . . . 20 cm + 2 ppm  
 After 20 minutes . . . . . 10 cm + 2 ppm  
 After 45 minutes . . . . . 1 cm + 2 ppm

## temperature

Operation . . . . . -20 °C to +50 °C (-4 °F to 122 °F)  
 Storage . . . . . -30 °C to +70 °C (-22 °F to 158 °F)  
 Charging . . . . . 0 °C to +45 °C (32 °F to 113 °F)

## mechanical shock

Drop . . . . . 1.2 m (4 ft) concrete under plywood  
 Vibration . . . . . Method 514.5

## altitude and humidity ratings

Relative humidity . . . . . 95% non-condensing  
 Maximum operating altitude . . . . . 3,658 m (12,000 ft)  
 Maximum storage altitude . . . . . 5,000 m (16,400 ft)

## ingress protection

Water/Dust . . . . . IP65

## Battery

Type . . . . . Rechargeable, removable Li-Ion  
 Capacity . . . . . 11.1V 2.5 AH  
 Charge time . . . . . 4 hours (typical)

## Battery run time

GNSS only . . . . . 11.5 hours  
 GNSS & VRS over BT . . . . . 11 hours  
 GNSS & VRS over Wi-Fi . . . . . 10 hours  
 GNSS & VRS over Cellular modem . . . . . 8.5 hours  
 Standby time . . . . . 50 days

## Buttons & Controls

- Power key
- Left & right application keys
- Camera key

## Connectors & Inputs

- Internal microphone and speaker
- Mini USB connector
- DE-9 serial via optional USB null modem converter
- External power connector
- SIM socket
- SDHC socket

## Camera

Still mode . . . . . Autofocus 5 MP  
 Still image format . . . . . JPG  
 Video mode . . . . . Up to VGA resolution  
 Video file format . . . . . WMV with audio

## Cellular & Wireless

UMTS/HSDPA . . . . . 850/900/2100 MHz  
 GPRS/EDGE . . . . . 850/900/1800/1900 MHz  
 Wi-Fi . . . . . 802.11 b/g  
 Bluetooth . . . . . Version 2.1 + EDR

## Display

Type . . . . . Transflective LED-backlit LCD  
 Size . . . . . 4.2" (diagonal)  
 Resolution . . . . . 480x640  
 Luminance . . . . . 280 cd/m<sup>2</sup>

## Hardware

Processor . . . . . TI OMAP 3503  
 RAM . . . . . 256 MB  
 Flash . . . . . 2 GB  
 External storage . . . . . SD/SDHC up to 32 GB

## Languages

- English (US), Spanish, French, Portuguese (Brazilian), Chinese (Simplified), Korean, Japanese, Russian

## IN the BOX

- GeoExplorer 6000 series handheld
- Pouch
- Hand strap
- USB data cable
- Rechargeable battery pack
- AC Power adaptor
- Screen protector kit
- Spare stylus & tether
- Documentation

## Optional Accessories

- Trimble GNSS antenna
- 1.5 m & 5 m external antenna
- Range pole kit for external antenna
- Backpack kit for external antenna
- Vehicle mount
- Hard carry case
- TDL 3G cellular modem
- GeoBeacon receiver
- USB null modem converter
- USB to serial converter cable

## Software Compatibility

- TerraSync
- Trimble GPS Controller for Esri ArcPad software
- Trimble GPS Controller software
- GNSS Connector software
- GPS Office software
- Trimble Geosension ArcGIS Desktop software
- Third party NMEA-based application

1 GLONASS tracking is available only if the Trimble Floodlight satellite shadow reduction option is activated.  
 2 SBAS (Satellite Based Augmentation System). Includes WAAS available in North America only, EGNOS available in Europe only, and MSAS available in Japan only.  
 3 HRMS refers to Horizontal Root Mean Squared accuracy, 1-sigma (68%). Except in conditions where most GNSS signals are affected by trees, or buildings, or other objects. 45 minute carrier postprocessed accuracy is limited to data collected within 10 km of the base station. Except when using VRS corrections, accuracy varies with proximity to base station by +1 ppm for code postprocessing and real-time. Carrier postprocessed accuracy varies with proximity to base station by +2 ppm.  
 4 Tested by Trimble with default system settings at 21°C ambient. Actual run time will vary with conditions of use  
 5 3.5G edition handhelds only. The GeoXT 3.5G edition handheld is PTCRB certified and can operate on supported networks that do not require carrier certification. Consult with your local reseller for more information.  
 6 Bluetooth and Wi-Fi type approvals are country specific. GeoExplorer 6000 series handhelds have Bluetooth and Wi-Fi approval in the U.S. and in most European countries. For further information please consult your local reseller.  
 7 NMEA output is an optional upgrade.

Specifications subject to change without notice.

© 2011, Trimble Navigation Limited. All rights reserved. Trimble, the Globe & Triangle logo, GeoExplorer, and GPS Pathfinder are trademarks of Trimble Navigation Limited, registered in the United States and in other countries. EVEREST, Floodlight, GeoBeacon, GeoXT, GPS Analyst, GPScorrect, H-Star, Maxwell, Tempest, TerraSync, and VRS are trademarks of Trimble Navigation Limited. Microsoft and Windows Mobile are either registered trademarks or trademarks of Microsoft Corporation in the United States and/or other countries. The Bluetooth word mark and logos are owned by the Bluetooth SIG, Inc. and any use of such marks by Trimble Navigation Limited is under license. All other trademarks are the property of their respective owners. PN 022501-255 (02/11)



**NORTH & SOUTH AMERICA**  
 Trimble Navigation Limited  
 10355 Westmoor Drive  
 Suite #100  
 Westminster, CO 80021  
 USA  
 +1-720-587-4574 Phone  
 +1-720-587-4878 Fax

**EUROPE & AFRICA**  
 Trimble Germany GmbH  
 Am Prime Parc 11  
 65479 Raunheim  
 GERMANY  
 +49-6142-2100-0 Phone  
 +49-6142-2100-550 Fax

**ASIA-PACIFIC & MIDDLE EAST**  
 Trimble Navigation  
 Singapore PTE Limited  
 80 Marine Parade Road  
 #22-06 Parkway Parade  
 Singapore, 449269  
 SINGAPORE  
 +65-6348-2212 Phone  
 +65-6348-2232 Fax

YOUR LOCAL TRIMBLE OFFICE OR REPRESENTATIVE



www.trimble.com  
 store.trimble.com